

NEW SELF-RETRACTING LIFELINES RANGE

Make your transition to the EN360:2023 standard easier with our direct equivalence guide and our recommendations for use in specific sectors.

	Old reference	New reference	Lanyard / Length	Applications	Sectors	Maximal capacity
MINIBLOC 	AN102 →	AN101S25	- Webbing 47 mm 2,5 m	- Vertical - Fall Factor 0	- Construction - Industries	150 KG
MAXIBLOC 	AN100 →	AN109C	- Galvanized steel cable 4mm 6, 10, 15 m	- Vertical - Fall Factor 0	- Construction - Industries, maintenance - Transport	150 KG
MEDBLOC 	AN13006C2 →	AN108S06	- Webbing 25 mm 6 m	- Vertical - Fall Factor 0	- Construction - Industries	130 KG
PROTECTOR ROUND 	AN150 →	AN181C	- Stainless steel cable 4.5mm 6, 10, 15 m	- Vertical - Fall Factor 0	- Construction - Industries - Oil and gas - Energies	150 KG
PROTECTOR LARGE 	AN180 →	AN181C	- Stainless steel cable 4.5mm 20, 30 m	- Vertical - Fall Factor 0	- Construction - Industries - Oil and gas - Energies	150 KG
PROTECTOR ELEVATOR 	TR018 →	AN181CW	- Stainless steel cable 4.5mm 20, 28 m	- Vertical - Fall Factor 0 - Rescue winch	- Water works - Confined spaces - Construction - Industries	Fall Arrest 150 KG Rescue 130 KG
PROTECTOR EXTRA LARGE 	AN190 →	AN191CX	- Stainless steel cable 4.8mm 40, 60 m	- Vertical - Fall Factor 0	- Construction - Oil and gas - Industries	100 KG